

GENERAL TECHNICAL CHARACTERISTICS

Multifuoco System© Fourspeed forced ventilation system. Warm air ducting up to 16 m

Dual Pow er System Two Independent fans capable of climate zone control

Multifunction remote control LCD display, timer, themostat and Multicomfort function

Programming Daily, weekly and weekend modes. Dual time settings

Remote Control System Optional kit for remote control of stove with a simple SMS

structure Enamelied steel with door, brazier and firebox in cast iron

Majolica cladding Unique large hand-made pleces


Air Glass System Self-cleaning ceramic glass resistant up to 750°C

Easy Cleaning Quick and easy maintenance, removable ash drawer

Wellness Hum Idifler with a roma diffuser

TECHNICAL DRAWING





67,5





P961

Designed to heat medium -large spaces, this stove fits in well with classic style surroundings.

COLOURS 🗸

TECHNICAL DATA

Room heating capacity (min- max)	m ³	200 - 345
Rated heat output (min-max)	kW	3,7-12,0
Poweradjustable (positions)		5
Nominal thermal efficiency	%	87,5
Consumption at rated heat output (min-max)	Kg/h	0,9 -2,7
Dimensions WxDxH	cm	67,5 x 60 x 116
Cladding/fiont		majolica
Тор		m a jolica - steel
Firebox		steel
Baffle plate/Firebox/Brazler		cast Iron
Flue outlet Ø	cm	08
Flue direction options		
Ash drawer		remova ble
Door		cast Iron
Ceramic glass		resistant up to 750°C
Doorhandle		steel with nichel plated finish
Hoppercapacity	Kg	35
Um Idifier in stainless steel		yes
Oven in stalniesssteel (LXWXH)	cm	no
Multifuoco System ©		4 levels speed
Dual Power		yes
Remote control		display LCD
Stove control panel		with digital controls
Timer-thermostat with programming		dally, weekly and week-end with two times
Remote Contiol System		optional
Front air ventso rientable		yes-yes
Lateral vents		
Minimum power consumption	Watt	150
Maximum power consumption	Watt	430
Total weight	Kg	193

Calculated based on nominal heat output and refers to room swith a thermal requirement between 0.060 and 0.035 kW perm $^{\rm 2}.$

The availability of models may vary from Country to Country.



