



IP 7

GENERAL TECHNICAL CHARACTERISTICS

- Structure: steel firebox, extractable with sliding tracks, firebox in cast iron, steel grate
- Door: cast iron, gasket with metal sheath resistant to high temperature, ceramic glass resistant up to 750°C
- Flue outlet \varnothing cm: 8
- Function control: with multilingual display
- Programming: daily, weekly and weekend dual time settings
- Energy Saving: automatic ignition and based on set ambient temperature
- Eco Function: automatic control of the fire

OPTIONAL:

- Front pellet loading tray kit
- Front pellet loading kit, side and additional tank
- Adjustable legs kit

TECHNICAL DATA

Room heating capacity	m ²	115 - 195
Nominal thermal efficiency	%	80,5 - 85,5
Rated heat output (min-max)	KW	2,9 - 6,8
Consumption at rated heat output (min-max)	Kg/h	0,8 - 1,7
Power settings		4
Hopper capacity	Kg	8
Flue outlet	\varnothing cm	8
Fresh air intake (recomm. m in sect.)	\varnothing cm ²	100
Electric supply	Hz	230 - 50
Electric power consumption	W	110 - 400
Weight	Kg	100



The availability of models may vary from Country to Country.

Full technical data available in pdf

Compatible Cover

TECHNICAL DRAWING

