



P958 T

The classic style of round stoves is restyled with a fashionable modern design.

COLOURS



GENERAL TECHNICAL CHARACTERISTICS

Multiflue System®

4 speed forced ventilation system. Warm air ducting up to 16 m

App

This allows you to manage all stove features with ease via smartphone and tablet.

Multifunction remote control

LCD display, timer, thermostat and Multiflue control function

Programming

Daily, weekly and weekend modes. 6 time settings

Remote Control System

Optional kit for remote control of stove with a simple SMS

Structure

Enamelled steel with door, brazier in cast iron

Majolica cladding

Unique large hand-made pieces

Air Glass System

Self-cleaning ceramic glass resistant up to 750°C

Energy Saving

Quick and easy maintenance, removable ash drawer

Wellness

Humidifier with aroma diffuser

Eco function

Automatic power control of the fire


Pellet Level Sensor

Allows to monitor the amount of pellet in the hopper, displaying an alert when refilling is required.

Easy cleaning system

Ash vacuum cleaner standard

TECHNICAL DRAWING



TECHNICAL DATA

Room heating capacity (min-max)	m ²	145 - 250
Rated heat output (min-max)	kW	2,7 - 8,6
Power adjustable (positions)		4
Nominal thermal efficiency	%	89,3
Consumption at rated heat output (min-max)	Kg/h	0,6 - 1,9
Dimensions WxDxH	cm	54 x 53 x 109
Cladding/front		Majolica
Top		Rolling Top
Firebox		steel
Baffle plate/Firebox/Brazier		steel / cast iron
Flue outlet Ø	cm	8
Flue direction options		
Ash drawer		yes
Door		cast iron
Ceramic glass		resistant up to 750°C
Door handle		steel with nickel-plated finish
Hopper capacity	Kg	16
Umidifier in stainless steel		yes
Oven in stainless steel (LxWxH)	cm	
Multiflue System®		4 fan speed levels
Dual Power		No
Remote control		Yes
Stove control panel		Display with digital controls
Timer/thermostat with programming		6 daily time
Remote Control System		optional
Front air ventso ntable		yes - yes
Lateral vents		No
Minimum power consumption	Watt	100
Maximum power consumption	Watt	390
Total weight	Kg	148

Calculated based on nominal heat output and refers to rooms with a thermal requirement between 0.060 and 0.035 kW per m².

The availability of models may vary from Country to Country.

Copyright c 2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, anche parziale, in qualsiasi forma, delle fotografie e dei testi. I trasgressori saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. Il marchio ed i segni distintivi della società sono di proprietà esclusiva della satessa.

Poichè l'azienda è costantemente impegnata nel continuo perfezionamento di tutta la sua produzione, le caratteristiche estetiche e dimensionali, i dati tecnici e gli accessori possono essere soggetti a variazione.

Numero Verde
800-842026
www.piazzetta.it

